

Claim Amendments

1. (Currently Amendment) A method for generating cool air, comprising:
contacting a wastewater with a superabsorbent polymer;
allowing the superabsorbent polymer and the wastewater to interact until substantially all
of the wastewater is absorbed by the superabsorbent polymer; and
evaporating the water from the superabsorbent polymer, wherein evaporating the water is
facilitated by the use of a fan.
2. (Original) The method of claim 1 wherein the evaporating step is performed in the
presence of a heat exchanger.
3. (Original) The method of claim 1 wherein the superabsorbent polymer is an organic
cross-linked acrylamide/acrylic acid copolymer.
4. (Original) The method of claim 1 wherein the superabsorbent polymer is added to the
wastewater in an amount of from about 2 grams to about 200 grams per liter of wastewater.
5. (Cancelled)
6. (Withdrawn) An apparatus for treating wastewater comprising:
a floor;
two side walls connected to the floor;
a top connected to the walls, the top having perforations;
a superabsorbent polymer positioned above the top, the polymer having absorbed
wastewater;
an air moving device for moving air through the perforations and across the polymer such
that water from the wastewater undergoes an evaporation process.

7. (Withdrawn) The apparatus of claim 6 wherein the evaporation process has a cooling effect.
8. (Withdrawn) The apparatus of claim 7 further comprising a first air passageway for routing the air through the top.
9. (Withdrawn) The apparatus of claim 8 further comprising a second air passageway for collecting cooled air.
10. (Withdrawn) The apparatus of claim 9 further comprising a plenum for distributing cooled air.
11. (Withdrawn) The apparatus of claim 10 wherein the wastewater is produced by an animal rearing facility.
12. (Withdrawn) The apparatus of claim 11 contiguous with the animal rearing facility.
13. (Currently Amended) A method for generating cool air utilizing superabsorbent polymers, comprising:
- providing a perforated top;
 - placing a superabsorbent polymer that has absorbed water in a space above the top [device]; and
 - forcing air through the top across the polymer such that the absorbed water is evaporated.
14. (Original) The method of claim 13 further comprising collecting cool air from a passageway adjacent the top.
15. (Original) The method of claim 13 wherein the superabsorbent polymer is an organic cross-linked acrylamide/acrylic acid copolymer.
16. (Original) The method of claim 13 wherein the water is a wastewater.

17. (Original) The method of claim 16 wherein the wastewater is a wastewater from an animal rearing facility.

18. (New) A method for generating cool air utilizing superabsorbent polymers, comprising:

providing a perforated structure;

placing a superabsorbent polymer in a space adjacent the perforated structure;

absorbing water with the superabsorbent polymer; and

forcing air through the perforated structure such that the absorbed water in the polymer is evaporated.

19. (New) The method of claim 18 further comprising collecting cool air from a passageway adjacent perforated structure.

20. (New) The method of claim 18 wherein the superabsorbent polymer is an organic cross-linked acrylamide/acrylic acid copolymer.

21. (New) The method of claim 18 wherein the water is a wastewater.

22. (New) The method of claim 21 wherein the wastewater is a wastewater from an animal rearing facility.